

Desktop safes



SÚA

An excellent anti-theft (**certified S2**) and fireproof (**certified LFS 60P**) safe  
Built with a double inter-welded wall and filled with fire-resistant concrete



FEATURES

- Thickness (front / casing): 105 mm / 77 mm. Laser cut.
- **Fire resistance:** withstands interior temperature of up to 170°C for up to 1 hour (paper decomposes at 177°C).
- Rotating bolts (anti-saw system)
- Housing for bolts (anti-lever system).
- Includes fixing screws.
- Fixing holes: 1 on the base.

LOCKING SYSTEM

- Electronic + mortice key (except ref. 400140, which only has an electronic lock).
- Opening codes: 2.
- Master function.
- Dual Code function.
- Programmable opening delay from 1 to 99 minutes.
- Lockout after three failed opening attempts.
- Low battery warning with red LED light.
- Power supply: 1 9V battery.




SÚA  
Ref. 400050  
Electronic opening + key




Ref. 400140. Electronic opening



Ref. 400050



400140



400050

Ref.	Exterior measurements (H x W x D) mm	Interior measurements (H x W x D) mm	Kg	L	Shelf	No. of bolts	Bolts position	EAN13 code 8425181 *	Pack. measurement (H x W x D) mm
400140	490x480x460	330x332x300	85 kg.	33 L.	1	4 + 2		* 744970	530x500x490
400050	670x480x460	510x332x300	108 kg.	51 L.	1	4 + 2		* 744987	710x500x490